

Portable GSM Data Transmitter for Sebalog N-3 and Sebalog P-3

Special features

- Offers remote data transmission
- Fits even into small valve boxes
- Uses field replaceable batteries
- Is fully submersible
- Operates wireless
- Carries data from up to three devices

Description

Patrolling noise and pressure loggers is time consuming and costly. The GSM Transmitter 3 (GT-3) can save you this trouble. It is designed to transmit data collected by noise and pressure loggers from the site to your office. Using GSM/GPRS, on site patrolling is no longer necessary. Save time, money and monitor your network from the office with the GT-3.

Small and fully submersible, the GSM Transmitter 3 is specifically designed to fit into valve boxes and hydrant chambers.

Always ready to use - the GSM Transmitter 3 is equipped with two powerful field-replaceable batteries.

Up to three devices can be connected to the GSM Transmitter 3 - a benchmark in cost efficiency for GSM data transmission out of an underground chamber.

The fully wireless operation offers the best flexibility to place and mount the GT-3 inside a chamber.



Technical data

Dimensions (incl. antenna)	44 x 44 x 124mm (44 x 44 x 160mm)
Weight	225 g
Power supply	2 x AA 1.5 V Lithium
Operating time	1 year (depending upon use)
Operating temperature	-20 °C ... +60 °C
Data transmission	GPRS
Alarm targets	SMS, Email
Communication	Bi-directional radio
IP protection class	IP 68

