

## Technical data

<b>Sebalog D-3</b>	
Protection class	IP68
Temperature range	-20° C bis +60° C
State control	LED
Weight	900 g
Dimensions	185 mm x 115 mm
<b>Power supply</b>	
Internal lithium battery	Up to 5 years (standard configuration)
External battery	Optional
External Power supply via VK 76	12 V 1.5 A
<b>Input (max. 4)</b>	
Digital	4, frequency/pulse
Analogue	2, 0 ... 5 V / 0 ... 20 mA
Relays input	2
Relays output	2
<b>Collection of data</b>	
Internal pressure sensors	0 -16 bar (standard), 25 bar, 35 bar
Recording interval	1 sec - 24 h
Memory	Up to 1.7 Mio. measurements
External memory	SebaCloud
Alarm messages	SMS, e-mail
<b>Communication</b>	
SebaCloud 7 FTP server	SebaDataView-3 / SCADA / GIS
Communication	GSM / GPRS / 3G / UMTS



### SebaKMT

Dr.-Herbert-lann-Str.6 · D-96148 Baunach  
Tel. +49 (0) 95 44 - 6 80 · Fax +49 (0) 95 44 - 22 73  
sales@sebakmt.com · [www.sebakmt.com](http://www.sebakmt.com)