



VIVAX
METROTECH

VM-550FF & VM-560FF Transmitters

Technical Specifications V1.1



Worldwide Locations

World Headquarters, United States of America

Vivax-Metrotech Corporation

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-1400

Fax : +1-408-734-1415

Website : www.vivax-metrotech.com

Email : SalesUSA@vxmt.com

Central/South America and the Caribbean

Ventas para América Latina

3251 Olcott Street, Santa Clara, CA 95054, USA

T/Free : 1-800-446-3392

Tel : +1-408-734-1400

Fax : +1-408-743-5597

Website : www.vivax-metrotech.com

Email : LatinSales@vxmt.com

Canada

Vivax Canada, Inc.

41 Courtland Ave Unit 8, Vaughan, ON L4K 3T3, Canada

Tel : +1-289-846-3010

Fax : +1-905-752-0214

Website : www.vivax-metrotech.com

Email : SalesCA@vxmt.com

United Kingdom

Vivax-Metrotech Ltd.

Unit 1, B/C Polden Business Centre, Bristol Road, Bridgwater, Somerset, TA6 4AW, UK

Tel : +44(0)1793 822679

Website : www.vivax-metrotech.com

Email : SalesUK@vxmt.com

France

Vivax-Metrotech SAS

Technoparc - 1 allée du Moulin Berger, 69130 Ecully, France

Tel : +33(0)4 72 53 03 03

Fax : +33(0)4 72 53 03 13

Website : www.vivax-metrotech.fr

Email : SalesFR@vxmt.com

Germany

Metrotech Vertriebs GmbH

Am steinernen Kreuz 10a
D-96110 Schesslitz

Tel : +49 954 277 227 43

Website : www.vivax-metrotech.de

Email : SalesEU@vxmt.com

A. Typical Applications

Item	Parameter
Description	VM-550FF and VM-560FF Transmitters
Uses	Transmitting active signals for the location of buried pipes and cables Transmitting a fault-find frequency for the detection of cable faults Transmitting active signals for the location of camera systems pushrod cable

B. Characteristics

Item	Parameter																		
Construction	High-impact ABS plastic																		
Weight	With Alkaline batteries: 2.47 lbs. (1.12kg) With Rechargeable Li-ion batteries: 2 lbs. (0.92 kg.)																		
Dimensions	18.1in(L) x 3.5in(W) x 2.6in(H) (460mm x 90mm x 65mm)																		
Display	None, flashing red LED lights show active transmit and output modes																		
Power Supply	4 x Alkaline "D" cells Optional Li-Ion rechargeable battery pack																		
Battery Life	<table border="1" style="width: 100%; text-align: center;"> <thead> <tr> <th>Transmitter</th> <th>Output Power</th> <th>Alkaline</th> <th>Li-Ion (Rechargeable)</th> </tr> </thead> <tbody> <tr> <td rowspan="2">VM-550FF</td> <td>Full Power</td> <td>13 hours</td> <td>17 hours</td> </tr> <tr> <td>Low Power</td> <td>44 hours</td> <td>45 hours</td> </tr> <tr> <td rowspan="2">VM-560FF</td> <td>Full Power</td> <td>20 hours</td> <td>29 hours</td> </tr> <tr> <td>Low Power</td> <td>48 hours</td> <td>48 hours</td> </tr> </tbody> </table>	Transmitter	Output Power	Alkaline	Li-Ion (Rechargeable)	VM-550FF	Full Power	13 hours	17 hours	Low Power	44 hours	45 hours	VM-560FF	Full Power	20 hours	29 hours	Low Power	48 hours	48 hours
	Transmitter	Output Power	Alkaline	Li-Ion (Rechargeable)															
	VM-550FF	Full Power	13 hours	17 hours															
		Low Power	44 hours	45 hours															
VM-560FF	Full Power	20 hours	29 hours																
	Low Power	48 hours	48 hours																
At 70° F (21° C) - continuous use																			
Li-Ion batteries will withstand 500 charging life cycles																			
Environmental	IP54 and NEMA 4																		
External Connectors	1 x 3 pin XLR socket																		
Temperature Range	Operating: -4°F to 122°F (-20°C to 50°C) Storage: -40°F to 140°F (-40°C to 60°C)																		
Compliance/Approvals	<ul style="list-style-type: none"> - Complies with European standard CE (Directive 99/5/EC) <ul style="list-style-type: none"> • EN 55011, EN 61000-4-3, EN 61000-4-2, EN 61000-4-4, EN 61000-4-5, EN 61000-4-8 - Complies with FCC Rules Part 15 - CFR 47 Part 15 																		

Standard Accessories (Supplied with Transmitter)	<ul style="list-style-type: none"> - Direct Connection Leads (XLR plug with 10-foot (3.5m) red/black leads) - Ground stake - Alkaline batteries - User guide
Compatible Accessories Options	<ul style="list-style-type: none"> - Li-ion rechargeable battery and charger - 2-inch (50mm) transmitter clamp - 4-inch (100mm) transmitter clamp - 5-inch (150mm) transmitter clamp - Live Plug Connector - Live Cable Connector - Ground Extension Spool
Frequencies	<ul style="list-style-type: none"> - Direct connection mode / Clamp mode: VM-550FF: 512Hz or 640Hz, 8.192kHz, and 83.1kHz VM-560FF: 512Hz or 640Hz, 8.192kHz, and 480kHz - Induction Mode: VM-550FF: 83.1kHz VM-560FF: 480kHz - Fault Find Mode: VM-550FF, VM-560FF <p>8kFF, Fault locating mode for use with vLoc accessory A-frame or VM-510 ground fault locator (8.192kHz amplitude modulated with 8Hz and phase-modulated with 2.66Hz)</p> <p>* Modes are automatically selected when accessories are plugged in.</p>

C. Operational

Item	Parameter
Information Displayed	<p>Solid and blinking LED shows</p> <ul style="list-style-type: none"> - Frequency selected - Output power level
Transmitting Modes	<p>Induction mode – applies signal inductively using the internal antenna -</p> <p>Direct connection mode – applies signal directly to the cable by clipping one output lead to the cable, the other to an independent ground -</p> <p>Clamp mode – applies signal using an inductive clamp (aka toroid or coupler) that is placed around the target pipe or cable</p> <p>* Modes are automatically selected when accessories are plugged in. The default mode (no accessories) is Induction.</p>

Transmitting Frequency by Mode	<ul style="list-style-type: none"> - Direct connection mode / Clamp mode: VM-550FF: 512Hz or 640Hz, 8.192kHz, and 83.1kHz VM-560FF: 512Hz or 640Hz, 8.192kHz, and 480kHz - Induction Mode: VM-550FF: 83.1kHz VM-560FF: 480kHz - Fault Find Mode: VM-550FF, VM-560FF 8kFF, Fault locating mode for use with vLoc accessory A-frame or VM-510 ground fault locator (8.192kHz amplitude modulated with 8Hz and phase-modulated with 2.66Hz) <p>* Modes are selected automatically when accessories are plugged in.</p>
Power Output	<ul style="list-style-type: none"> - Per FCC part 15: <ul style="list-style-type: none"> • 1 watt – in High output level • 0.1 watt – in Low output level
Maximum Output Voltage	60V RMS
Output Current	Maximum output current = 70mA RMS constant current
Output Protection	Output protected against accidental connection to up to 240V AC
Audio indication	<ul style="list-style-type: none"> - Connection quality – variable beep rate sound showing the better signal applied - Beep constantly – for high voltage detected
Controls	<p>Use pushbuttons to select:</p> <ul style="list-style-type: none"> - Power button: On / Off (Press and hold) - Low / High output (Short press) - Frequency
Compatible Receivers	VM-550, VM-560, VM-585, VM-510FFL+, vLoc3-Cam

D. Rechargeable Battery (optional accessory)

Item	Parameter
Description	<p>Custom Lithium-Ion battery pack and charger</p> <p>Li-Ion batteries will withstand 500 charging life cycles</p>
Input/output	<p>Input: 8.4V ~ 8.5V</p> <p>Output: 6V~8.4V</p>
Temperature Range	Operating: 14°F to 140°F (-10°C to 60°C)

	Storage : 14°F to 113°F (-10°C to 45°C)
Storage Humidity	≤75% RH
Weight	1.26lb (0.57kg)
Dimensions	8.3in(L) x 3.7in(W) x 2.5in(H) (210mm x 93mm x 63mm)
Shipping Weight	1.38lb (0.63kg)
Shipping Dimensions	9in(L) x 3.7in(W) x 2.8in(H) (228mm x 95mm x 70mm)
Warranty	12 months

E. Shipping and Packaging

Item	Parameter		
Shipping Weight	Transmitter	with Alkaline Batteries	with Li-ion and charger
	VM-550FF	9.3lbs (4.2kg)	8.82lbs (4kg)
	VM-560FF	9.48lbs (4.3kg)	9lbs (4.1kg)
Shipping Dimension	39in(L) x 7.7in(W) x 4.7in(H) (990mm x 195mm x 120mm)		

F. Warranty

Item	Parameter
Warranty	<ul style="list-style-type: none"> - 12 months - Extended warranty available

All products are designed and manufactured per ISO 9001:2015.

Disclaimer: Product and accessory specification and availability information are subject to change without prior notice.